The Inventory Management System has been designed to operate with most properly interfaced matrix printers on the market. When you set the Configuration File (II-12) for a matrix printer (m), then the program will use expanded type for headings and regular type for the body of reports. If you do not want this expanded feature, set the Configuration File to (q).

Different printers use different control characters for expanded print and regular print. If you are not using the Vic-1525 matrix printer, then you will have to change the control characters for expanded/regular print. The following table shows the value of A and B that you must assign in a small program to work properly with these printers:

Printer	A =	B =
VIC-1525	14	15
CBM-4022 or 2022	1	129
CBM-8023P	1	129
Mannesman Tally	1	129

For other printers, call Info-Designs Customer Support Services - (313) 540-7772

MAKING THE PROGRAM CHANGE

You must change the program "i/c" (on side 1 of the program disk) if you are not using the VIC-1525. This change is only required one time, then your system will operate correctly, if you have followed these directions properly. Follow these steps - EXACTLY:

1) Turn your system off, wait 2 seconds, turn system on
2) Make sure the notch on the program disk is exposed-
   Insert I/M Program Disk into Disk Drive
   (Drive 0 if using a CBM-4040)
3) Enter: **load"i/c",8** then press <RETURN>
4) Enter: **15 a=x: b=y** then press <RETURN>
   (where x and y are the values from the above table)
   Example: for CBM:4022, enter **15 a=1: b=129**
5) Enter: **list 15** then press <RETURN>
   (verify that your statement was entered correctly)
6) Enter: **open15,8,15,"s0:i/c":close15** then press <RETURN>
7) Enter: **save"i/c",8** then press <RETURN>
8) Enter: **verify"*",8** then press <RETURN>
   (Screen should print **OK**. If you get a verify error then repeat steps 6 - 8)

NOTE: BE CAREFUL TO ENTER ONLY THE ABOVE COMMANDS! ANY OTHER KEYSTROKES COULD DESTROY THIS PROGRAM WHICH WILL CAUSE A SYNTAX ERROR WHEN YOU RUN THE SYSTEM.

IF YOU DESTROY THE PROGRAM YOU WILL HAVE TO ORDER A REPLACEMENT DISK AT $25.00, SO BE VERY CAREFUL.

Now enter run <RETURN> and the A/R system will run correctly, if you have followed the above directions.

© 1983 IDI